

The ExSol package*

Walter Daems (`walter.daems@ua.ac.be`)

1 Introduction

The package `ExSol` provides macros to allow embedding exercises and solutions in the \LaTeX source of an instructional text (e.g., a book or a course text) while generating the following separate documents:

- your original text that only contains the exercises, and
- a solution book that only contains the solutions to the exercises (a package option exists to also copy the exercises themselves to the solution book).

The former is generated when running \LaTeX on your document. This run writes the solutions to a secondary file that can be included into a simple document harness, such that when running \LaTeX on the latter, you can generate a nice solution book.

Why use `ExSol`?

- It allows to keep the \LaTeX source of your exercises and their solutions in a single file. Away with the nightmare to keep your solutions in sync with the original text.
- It separates exercises and solutions, allowing you
 - to only release the solution book to the instructors of the course;

*This document corresponds to `exsol` 0.7, dated 2014/07/14.

- to encourage students that you provide with the solution book to first try solving the exercises without opening the book; this seems to be easier than not peeking into the solution of an exercise that is typeset just below the exercise itself.

The code of the ExSol package was taken almost literally from `fancyvrb` [1]. Therefore, all credits go to the authors/maintainers of `fancyvrb`.

Thanks to Pieter Pareit and Pekka Pere for signaling problems and making suggestions for the documentation.

2 Installation

Either you are a package manager and then you'll know how to prepare an installation package for ExSol.

Either you are a normal user and then you have two options. First, check if there is a package that your favorite L^AT_EX distributor has prepared for you. Second, grab the TDS package from CTAN [2] (`exsol.tds.zip`) and unzip it somewhere in your own TDS tree, regenerate your filename database and off you go. In any case, make sure that L^AT_EX finds the `exsol.sty` file.

The ExSol package uses some auxiliary packages: `fancyvrb`, `ifthen`, `kvoptions` and, optionally, `babel`. Fetch them from CTAN [2] if your T_EX distributor does not provide them.

3 Usage

3.1 Preparing your document source

The macro package `exsol` can be loaded with:

```
\usepackage{exsol}
```

Then, you are ready to add some exercises including their solution to your document source. To this end, embed them in a `exercise` and a corresponding `solution` environment. Optionally, you may embed several of

them in a `exercises` environment, to make them stand out in your text.
E.g.,

```

\begin{exercises}

\begin{exercise}
  Solve the following equation for  $x \in \mathbb{C}$ , with  $\mathbb{C}$  the set of
  complex numbers:
  \begin{equation}
    5x^2 - 3x = 5
  \end{equation}
\end{exercise}

\begin{solution}
  Let's start by rearranging the equation, a bit:
  \begin{equation}
    5.7x^2 - 3.1x = 5.3 \\
    5.7x^2 - 3.1x - 5.3 = 0
  \end{equation}
  The equation is now in the standard form:
  \begin{equation}
    ax^2 + bx + c = 0
  \end{equation}
  For quadratic equations in the standard form, we know that two
  solutions exist:
  \begin{equation}
    x_{1,2} = \frac{-b \pm \sqrt{d}}{2a}
  \end{equation}
  with
  \begin{equation}
    d = b^2 - 4ac
  \end{equation}
  If we apply this to our case, we obtain:
  \begin{equation}
    d = (-3.1)^2 - 4 \cdot 5.7 \cdot (-5.3) = 130.45
  \end{equation}
  and
  \begin{equation}
    x_1 = \frac{3.1 + \sqrt{130.45}}{11.4} = 1.27 \\
    x_2 = \frac{3.1 - \sqrt{130.45}}{11.4} = -0.73
  \end{equation}
  The proposed values  $x = x_1, x_2$  are solutions to the given equation.
\end{solution}

\begin{exercise}
  Consider a 2-dimensional vector space equipped with a Euclidean
  distance function. Given a right-angled triangle, with the sides

```

```

    $A$ and $B$ adjacent to the right angle having lengths, $3$ and
    $4$, calculate the length of the hypotenuse, labeled $C$.
\end{exercise}
\begin{solution}
    This calls for application of Pythagoras' theorem, which
    tells us:
    \begin{equation}
        \left|A\right|^2 + \left|B\right|^2 = \left|C\right|^2
    \end{equation}
    and therefore:
    \begin{eqnarray}
        \left|C\right| \\
        &= \sqrt{\left|A\right|^2 + \left|B\right|^2} \\
        &= \sqrt{3^2 + 4^2} \\
        &= \sqrt{25} = 5
    \end{eqnarray}
    Therefore, the length of the hypotenuse equals $5$.
\end{solution}

\end{exercises}

```

The result in the original document, can be seen below. As you can see, there's no trace of the solution.

Exercises

Exercise 3.1-1: Solve the following equation for $x \in C$, with C the set of complex numbers:

$$5x^2 - 3x = 5 \tag{1}$$

Exercise 3.1-2: Consider a 2-dimensional vector space equipped with a Euclidean distance function. Given a right-angled triangle, with the sides A and B adjacent to the right angle having lengths, 3 and 4, calculate the length of the hypotenuse, labeled C .

When running L^AT_EX on your document (in our case on the `exsol.dtx` file, as a side effect a file with extension `.sol.tex` has been written to disk (in our case, the file `exsol.sol.tex`), containing all solutions in sequence.

Generating a solution book is as simple as including the file into a simple harness, that allows you giving it a proper title page and to add other bells and whistles.

E.g.,

```

\documentclass{article}
\usepackage[english]{babel}
\title{Solutions to the exercises, specified in the \textsf{ExSol} package}
\author{Walter Daems}
\date{2013/05/12}

\begin{document}

\maketitle

\input{exsol.sol}

\end{document}

```

You may generate this solution book, by running \LaTeX on the file named `exsol-solutionbook.tex` that is generated when running \LaTeX on the `exsol.dtx` file.

The result approximately looks like this:

Solutions to the exercises, specified in the **ExSol** package
Walter Daems
2013/05/12

Solution 3.1-1 Let's start by rearranging the equation, a bit:

$$5.7x^2 - 3.1x = 5.3 \quad (1)$$

$$5.7x^2 - 3.1x - 5.3 = 0 \quad (2)$$

The equation is now in the standard form:

$$ax^2 + bx + c = 0 \quad (3)$$

For quadratic equations in the standard form, we know that two solutions exist:

$$x_{1,2} = \frac{-b \pm \sqrt{d}}{2a} \quad (4)$$

with

$$d = b^2 - 4ac \quad (5)$$

If we apply this to our case, we obtain:

$$d = (-3.1)^2 - 4 \cdot 5.7 \cdot (-5.3) = 130.45 \quad (6)$$

and

$$x_1 = \frac{3.1 + \sqrt{130.45}}{11.4} = 1.27 \quad (7)$$

$$x_2 = \frac{3.1 - \sqrt{130.45}}{11.4} = -0.73 \quad (8)$$

The proposed values $x = x_1, x_2$ are solutions to the given equation.

Solution 3.1-2 This calls for application of Pythagoras' theorem, which tells us:

$$\|A\|^2 + \|B\|^2 = \|C\|^2 \quad (9)$$

and therefore:

$$\|C\| = \sqrt{\|A\|^2 + \|B\|^2} \quad (10)$$

$$= \sqrt{3^2 + 4^2} \quad (11)$$

$$= \sqrt{25} = 5 \quad (12)$$

Therefore, the length of the hypotenuse equals 5.

3.2 Tips and tricks

Just one for now: if you want to include the solutions all at the end of the current document, you need to explicitly close the solution stream before including it:

```
\closeout\solutionstream\input{\jobname.sol.tex}
```

4 Implementation

```
1 <*package>
```

4.1 Auxiliary packages

The package uses some auxiliary packages:

```
2 \RequirePackage{fancyvrb}
3 \RequirePackage{ifthen}
4 \RequirePackage{kvoptions}
```

4.2 Package options

The package offers some options:

exercisefontsize This option allows setting the font of the **exercises** environment. You may choose one of tiny, scriptsize, footnotesize, small, normalsize, large, etc.
E.g., `[exercisefontsize=small]`.

```
5 \DeclareStringOption[normalsize]{exercisefontsize}
```

exerciseaslist This boolean option (true, false) allows setting the typesetting of the **exercises** in a list environment. This causes the exercises to be typeset in a more compact fashion, with indented left and right margin.

```
6 \DeclareBoolOption[false]{exerciseaslist}
```

copyexercisessolutions This boolean option (true, false) allows copying the exercises in the solutions file, to allow for making a complete stand-alone exercises bundle.

```
7 \DeclareBoolOption[false]{copyexercisessolutions}
```

The options are processed using:

```
8 \ProcessKeyvalOptions*
```

The options are subsequently handled

```
9 \newcommand{\exercisefontsize}{\csname \exsol@exercisefontsize\endcsname}
```

4.3 Con- and destruction of the auxiliary streams

At the beginning of your document, we start by opening a stream to a file that will be used to write the solutions to. At the end of your document, the package closes the stream.

```
10 \AtBeginDocument{
11   \newwrite\solutionstream
12   \immediate\openout\solutionstream=\jobname.sol.tex
13 }
14 \AtEndDocument{
15   \immediate\closeout\solutionstream
16 }
```

4.4 Exercises counter

By providing an exercise counter, proper numbering of the exercises is provided to allow for good cross referencing of the solutions to the exercises.

```
17 \newcounter{exercise}[subsection]
18 \setcounter{exercise}{0}
19 \renewcommand{\theexercise}{%
20   \@ifundefined{c@chapter}{\if0\arabic{chapter}\else\arabic{chapter}.\fi}%
21   \if0\arabic{section}\else\arabic{section}\fi%
22   \if0\arabic{subsection}\else.\arabic{subsection}\fi%
23   \if0\arabic{subsubsection}\else.\arabic{subsubsection}\fi%
24   \if0\arabic{exercise}\else%
25     \@ifundefined{c@chapter}%
26       {\if0\arabic{section}\else-\fi}%
27       {-}%
28   \arabic{exercise}%
29 \fi
30 }
```

4.5 Detokenization in order to cope with utf8

Combining old-school L^AT_EX (before X_YL^AT_EX and LuaT_EX) and UTF-8 is a pain. Detokenization has been suggested by Geoffrey Poore to solve issues with UTF-8 characters messing up the `fancyvrb` internals.

```
31 \newcommand{\GPES@write@detok}[1]{%
```



```

32 \immediate\write\exercisestream{\detokenize{#1}}}%
33 \newcommand{\GPSS@write@detok}[1]{%
34 \immediate\write\solutionstream{\detokenize{#1}}}%
35 \newcommand{\GPSS@write@detok}[1]{%
36 \GPES@write@detok{#1}%
37 \GPSS@write@detok{#1}}%

```

5 The user environments

exercise The **exercise** environment is used to typeset your exercises, provide them with a nice label and allow for copying the exercise to the solutions file (if the package option `copyexercisesinsolution`) is set. The label can be set by redefining the `\exercisename` macro, or by relying on the **Babel** provisions. The code is almost literally taken from the **fancyvrb** package.

```

38 \def\exercise{\FV@Environment}{\exercise}}
39 \def\FVB@exercise{%
40 \refstepcounter{exercise}%
41 \newwrite\exercisestream
42 \immediate\openout\exercisestream=\jobname.exc.tex
43 \ifxsol@copyexercisesinsolutions
44 \typeout{Writing exercise to \jobname.sol.tex}
45 \immediate\write\solutionstream{\string\par---\string\newline
46 \string\textbf{\string{\exercisename{}} \theexercise \string}}
47 \else
48 \immediate\write\solutionstream{\string\par---\string\newline}
49 \fi
50 \immediate\write\exercisestream{\string\begin{exsol@exercise}}
51 \@bsphack
52 \begingroup
53 \FV@UseKeyValues
54 \FV@DefineWhiteSpace
55 \def\FV@Space{\space}%
56 \FV@DefineTabOut
57 \ifxsol@copyexercisesinsolutions
58 \let\FV@ProcessLine\GPSS@write@detok %
59 \else
60 \let\FV@ProcessLine\GPES@write@detok %
61 \fi
62 \relax
63 \let\FV@FontScanPrep\relax
64 \let\@noligs\relax

```

```

65     \FV@Scan
66   }
67 \def\FVE@exercise{
68   \endgroup\@esphack
69   \immediate\write\exercisestream{\string\end{exsol@exercise}}
70   \ifexsol@copyexercisesinsolutions
71     \immediate\write\solutionstream{\string~\string\newline}
72   \fi
73   \immediate\closeout\exercisestream
74   \input{\jobname.exc.tex}
75 }
76 \DefineVerbatimEnvironment{exercise}{exercise}{}

```

exsol@exercise The **exsol@exercise** environment is an internal macro used to typeset your exercises and provide them with a nice label and number. Do not use it directly. Use the proper environment **exercise** instead.

```

77 \newenvironment{exsol@exercise}[0]
78 {%
79   \begin{minipage}[t]{\textwidth}%
80     \ifthenelse{\boolean{exsol@exerciseaslist}}
81       {\begin{list}%
82         {%
83           }%
84           {%
85             \setlength{\topsep}{0pt}%
86             \setlength{\leftmargin}{1em}%
87             \setlength{\rightmargin}{1em}%
88             \setlength{\listparindent}{0em}%
89             \setlength{\itemindent}{0em}%
90             \setlength{\parsep}{\parskip}}%
91           \item[\hspace*{\leftmargin}\textit{\exercisename{}
92                                                     \theexercise:}]
93         }%
94         {
95           \textit{\exercisename{} \theexercise:}~
96         }
97   }
98 {%
99   \ifthenelse{\boolean{exsol@exerciseaslist}}
100     {\end{list}}{}
101   \end{minipage}
102   \vspace{1ex}\par
103 }

```

solution The `solution` environment is used to typeset your solutions and provide them with a nice label and number that corresponds to the exercise that preceded this solution. Theno label can be set by redefining the `\solutionname` macro, or by relying on the Babel provisions. The code is almost literally taken from the `fancyvrb` package.

```

104 \def\solution{\FV@Environment{}}{solution}}
105 \def\FVB@solution{%
106   \typeout{Writing solution to \jobname.sol.tex}
107   \immediate\write\solutionstream{\string\textbf\string{\solutionname{}}\string}}
108   \ifexsol@copyexercisesinsolutions
109     \immediate\write\solutionstream{\string\newline}
110   \else
111     \immediate\write\solutionstream{\string\textbf\string{\theexercise\string}%
112                                     \string\newline}
113   \fi
114   \@bsphack
115   \begingroup
116     \FV@UseKeyValues
117     \FV@DefineWhiteSpace
118     \def\FV@Space{\space}%
119     \FV@DefineTabOut
120     \let\FV@ProcessLine\GPSS@write@detok %
121     \relax
122     \let\FV@FontScanPrep\relax
123     \let\@noligs\relax
124     \FV@Scan
125   }
126 \def\FVE@solution{\endgroup\@esphack}
127 \DefineVerbatimEnvironment{solution}{solution}{}

```

exercises The `exercises` environment helps typesetting your exercises to stand out from the rest of the text. You may use it at the end of a chapter, or just to group some exercises in the text.

```

128 \newenvironment{exercises}
129 {\par\exercisesfontsize\rule{.25\linewidth}{0.15mm}\~\~*~\~*%
130 \textbf{\normalsize \exercisename}\vspace*{1ex}\~\~}
131 {\~\~*\rule{.25\linewidth}{0.15mm}\par}

```

5.1 Some Babel provisions

`\exercisename` The exercise environment makes use of a label `Exercise` macro.

```
132 \newcommand{\exercisename}{Exercise}
```

`\exercisesname` The exercises environment makes use of a label `Exercises` macro.

```
133 \newcommand{\exercisesname}{Exercises}
```

`\solutionname` The solution environment makes use of a label `Solution` macro.

```
134 \newcommand{\solutionname}{Solution}
```

You may redefine these macros, but to help you out a little bit, we provide with some basic Babel auxiliaries. If you're a true polyglot and are willing to help me out by providing translations for other languages, I'm very willing to incorporate them into the code.

```
135 \addto\captionsdutch{%
136   \renewcommand{\exercisename}{Oefening}%
137   \renewcommand{\exercisesname}{Oefeningen}%
138   \renewcommand{\solutionname}{Oplossing}%
139   \renewcommand{\solutionsname}{Oplossingen}%
140 }
141 \addto\captionsgerman{%
142   \renewcommand{\exercisename}{Aufgabe}%
143   \renewcommand{\exercisesname}{Aufgaben}%
144   \renewcommand{\solutionname}{L"osung}%
145   \renewcommand{\solutionsname}{L"osungen}%
146 }
147 \addto\captionsfrench{%
148   \renewcommand{\exercisename}{Exercice}%
149   \renewcommand{\exercisesname}{Exercices}%
150   \renewcommand{\solutionname}{Solution}%
151   \renewcommand{\solutionsname}{Solutions}%
152 }
153 \addto\captionsfinnish{
154   \renewcommand{\exercisename}{Teht"av"a}%
155   \renewcommand{\exercisesname}{Teht"avi"a}%
156   \renewcommand{\solutionname}{Ratkaisu}%
157   \renewcommand{\solutionsname}{Ratkaisut}%
158 }
```

Now the final hack overloads the basic sectioning commands to make sure that they are copied into your solution book.

```

159 \let\exsol@@makechapterhead\@makechapterhead
160 \def\@makechapterhead#1{%
161   \immediate\write\solutionstream{\string\chapter{#1}}%
162   \exsol@@makechapterhead{#1}
163 }
164 \ifdefined\frontmatter
165   \let\exsol@@frontmatter\frontmatter
166   \def\frontmatter{%
167     \immediate\write\solutionstream{\string\frontmatter}%
168     \exsol@@frontmatter
169   }
170 \fi
171 \ifdefined\backmatter
172   \let\exsol@@backmatter\backmatter
173   \def\backmatter{%
174     \immediate\write\solutionstream{\string\backmatter}%
175     \exsol@@backmatter
176   }
177 \fi
178 \ifdefined\mainmatter
179   \let\exsol@@mainmatter\mainmatter
180   \def\mainmatter{%
181     \immediate\write\solutionstream{\string\mainmatter}%
182     \exsol@@mainmatter
183   }
184 \fi

```

`\noexerciseshapter` If you have chapters without exercises, you may want to indicate this clearly into your source. Otherwise empty chapters may appear in your solution book.

```

185 \newcommand{\noexerciseshapter}
186 {
187   \immediate\write\solutionstream{No exercises in this chapter}
188 }

189 </package>

```

References

- [1] Timothy Van Zandt, Herbert Voß, Denis Girou, Sebastian Rahtz, Niall Mansfield The `fancyvrb` package. <http://ctan.org/pkg/fancyvrb>. online, accessed in January 2012.
- [2] The Comprehensive TeX Archive Network. <http://www.ctan.org>. online, accessed in January 2012.

Change History

v0.1	General: . Initial version 1	Added option <code>exerciselinlist</code> . 7
v0.2	General: . Minor bug fixes based on first use by Paul Levrie . . 1	Changed name of option to <code>exercisefontsize</code> 7
	Added option <code>exercisefont</code> . . 7	<code>exsol@exercise</code> : Added option <code>exerciselinlist</code> such that default results in non list formatting of exercise 10
	Fixed babel errors 12	
	Removed dash in counter when in document without sectioning commands 8	v0.5
	<code>exercises</code> : Attempted to fix MiKTeX formatting problems 11	General: . Added option to also send exercises to solutions file 1
	<code>exsol@exercise</code> : Attempted to fix MiKTeX formatting problems 10	Added option <code>copyexerciselinlist</code> 7
v0.3		Changed option <code>exerciselinlist</code> to <code>exerciseaslist</code> 7
	General: . Minor bug fixes based on second use by Paul 1	<code>exsol@exercise</code> : Changed implementation to allow for copying the exercises to the solutions file. 10
	<code>exercises</code> : Added some extra whitespace below <code>exercisename</code> 11	v0.6
	<code>exsol@exercise</code> : Fixed <code>labelsep</code> to avoid cluttered itemize environments 10	General: . Prepared for CTAN publication 1
v0.4		v0.7
	General: . Allowed for non-list formatting of exercises (as default) 1	General: . Fixed UTF8 compatibility issues 1
		Added detokenized writing . . 8
		Added Finnish language support 12

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	\def 38,	F
\ 144, 145, 154, 155	39, 55, 67, 104,	\fi 20–23, 26,
\@bsphack 51, 114	105, 118, 126,	29, 49, 61, 72,
\@esphack 68, 126	160, 166, 173, 180	113, 170, 177, 184
\@ifundefined 20, 25	\DefineVerbatimEnvironment 76, 127	\frontmatter 164–167, 171
\@makechapterhead 159, 160	\detokenize 32, 34	\FV@DefineTabOut 56, 119
\@noligs 64, 123	E	\FV@DefineWhiteSpace 54, 117
\@ 129–131	\else 20–24, 26, 47, 59, 110	\FV@Environment 38, 104
A	\end 69, 100, 101	\FV@FontScanPrep 63, 122
\addto 135, 141, 147, 153	\endcsname 9	\FV@ProcessLine 58, 60, 120
\arabic 20–24, 26, 28	\endgroup 68, 126	\FV@Scan 65, 124
\AtBeginDocument 10	\exercise 38, <u>38</u>	\FV@Space 55, 118
\AtEndDocument 14	\exerciseaslist <u>6</u>	\FV@UseKeyValues 53, 116
B	\exercisename 46, 91, 95, <u>132</u> , 136, 142, 148, 154	\FVB@exercise 39
\backmatter 178–181	\exercises <u>128</u>	\FVB@solution 105
\begin 50, 79, 81	\exercisesfontsize <u>5</u> , 9, 129	\FVE@exercise 67
\begingroup 52, 115	\exercisename 130, <u>133</u> , 137, 143, 149, 155	\FVE@solution 126
\boolean 80, 99	\exercisestream 32, 41, 42, 50, 69, 73	G
C	\exsol@@backmatter 179, 182	\GPES@write@detok 31, 36, 60
\captionsdutch 135	\exsol@@frontmatter 165, 168	\GPES@write@detok 35, 58
\captionsfinnish 153	\exsol@@mainmatter 172, 175	\GPSS@write@detok 33, 37, 120
\captionsfrench 147	\exsol@@makechapterhead 159, 162	H
\captionsgerman 141	\exsol@exercise <u>77</u>	\hspace 91
\chapter 161	\exsol@exercisesfontsize 9	I
\closeout 15, 73		\if 20–24, 26
\copyexercisesinsolution <u>7</u>		
\csname 9		
D		
\DeclareBoolOption 6, 7		
\DeclareStringOption 5		

<code>\ifdefined</code>	<code>\newwrite</code> 11, 41	<code>\solutionsname</code> . . .
. . . 164, 171, 178	<code>\noexerciseshchapter</code>	139, 145, 151, 157
<code>\ifexsol@copyexerciseshinsolutions</code> <u>185</u>	<code>\normalsize</code> 130	<code>\solutionstream</code> . .
. . 43, 57, 70, 108		11, 12, 15, 34,
<code>\ifthenelse</code> . . 80, 99		45, 48, 71, 107,
<code>\immediate</code>	O	109, 111, 161,
12, 15, 32, 34,	<code>\openout</code> 12, 42	167, 174, 181, 187
42, 45, 48, 50,	P	<code>\space</code> 55, 118
69, 71, 73, 107,	<code>\par</code> 45, 48, 102, 129, 131	<code>\string</code> . 45, 46, 48,
109, 111, 161,	<code>\parsep</code> 90	50, 69, 71, 107,
167, 174, 181, 187	<code>\parskip</code> 90	109, 111, 112,
<code>\input</code> 74	<code>\ProcessKeyvalOptions</code>	161, 167, 174, 181
<code>\item</code> 91 8	T
<code>\itemindent</code> 89		<code>\textbf</code>
J	R	46, 107, 111, 130
<code>\jobname</code>	<code>\refstepcounter</code> . . 40	<code>\textit</code> 91, 95
12, 42, 44, 74, 106	<code>\relax</code> . 62–64, 121–123	<code>\textwidth</code> 79
L	<code>\renewcommand</code>	<code>\theexercise</code>
<code>\leftmargin</code> . . 86, 91 19, 136–	19, 46, 92, 95, 111
<code>\let</code> 58, 60, 63, 64,	139, 142–145,	<code>\topsep</code> 85
120, 122, 123,	148–151, 154–157	<code>\typeout</code> 44, 106
159, 165, 172, 179	<code>\RequirePackage</code> . 2–4	
<code>\linewidth</code> . . 129, 131	<code>\rightmargin</code> 87	
<code>\listparindent</code> . . 88	<code>\rule</code> 129, 131	V
M	S	<code>\vspace</code> 102, 130
<code>\mainmatter</code> . 172–174	<code>\setcounter</code> 18	W
N	<code>\setlength</code> . . . 85–90	<code>\write</code> 32, 34, 45, 48,
<code>\newcounter</code> 17	<code>\solution</code> . . . 104, <u>104</u>	50, 69, 71, 107,
<code>\newline</code> 45,	<code>\solutionname</code>	109, 111, 161,
48, 71, 109, 112 107, <u>134</u> ,	167, 174, 181, 187
	138, 144, 150, 156	